

NEXT  
GENERATION



# icountLaserCM30

Particle Contamination Monitor



ENGINEERING YOUR SUCCESS.



# Meet the Next Generation

## Particle Contamination Monitor - LCM30

The Parker icountLaserCM30 is a next generation fluid system contamination monitoring offering an under 90 seconds test procedure. Multi standard ISO 4406, NAS 1638, AS4059 & GOST cleanliness reporting, data entry and integral printing are all featured on this next generation contamination monitor.

Parker listened to their existing customers and then to the engineers and maintenance operatives to find out the features that have helped make the icountLaserCM a unique predictive maintenance instrument.



### What's New...

- Auto testing – start test from hand set
- Shorter test time - under 90 seconds
- Updated main enclosure
- Enhanced handset design
- Refined user interface
- Improved rechargeable battery life
- Integrated RH% moisture sensor and temperature
- Thermal printer (long life) improved data recording
- 8 x reported sizes (6 x measured / 2 x calculated) reporting codes to ISO4406 - NAS1638, AS4059 & GOST
- Now with RS232 Data Transfer over USB
- Easy to use 'Clip On' battery pack

### What's in the Case

1	Particle Contamination Monitor
1	Rechargeable Battery Pack
2	Printer Paper Roll (1 x fitted / 1 x spare)
1	USB cable
1	Flash Drive Memory Stick (inc. Manual and Download Software)
1	Quick Start Guide
1	Power Supply & Regional Power Cable



# Principle of Operation

### Why On-Site Fluid Contamination Monitoring?

- Certification of fluid cleanliness levels.
- Early warning instrument to help prevent catastrophic failure in critical systems.
- Comparable results to Laboratories
- To comply with customer cleanliness requirements and specifications.
- New equipment warranty compliance.
- New oil cleanliness testing.



The icountLaserCM30 is a Particle Contamination Monitor (PCM) that automatically sizes and counts individual particles suspended in a fluid using a laser illuminated optical light extinction principle.

The sensor uses a focused light source that is projected through oil moving in a flow cell; any particulate contamination within the oil will cause a change in signal proportional to its size on the detector. On-board flow metering delivers a precise volume of fluid through a flow cell at a controlled rate. Focused laser light is projected through fluid in the flow cell and any particulate contamination within the fluid reduces the amount of light that reaches the detector. The signals are processed and the particle size distribution is reported to the user.

Particle sizes are reported in micrometres [1x (10)<sup>-6</sup> metres] and displayed as "µm" for ISO Medium Test Dust (MTD) calibration or "µm" for Air Cleaner Fine Test Dust (ACFTD) calibration.

# Features & Benefits

- Special 'diagnostics' are incorporated into the icountLaserCM30 microprocessor control to ensure effective testing.
- Routine contamination monitoring of oil systems and liquid fuels with icountLaserCM30 saves time and saves money.
- Contamination monitoring is now possible during application operation - icountLaserCM30 saves on production downtime.
- Data entry allows individual equipment test log details to be recorded.
- Data retrieval of test results from memory via hand set display.
- Automatic test cycle logging of up to 1000 tests can be selected via hand set display.
- Totally portable, can be used as easily in the field as in the laboratory.
- Automatic calibration reminder.
- Instant results achieved with a test cycle in under 90 seconds.
- Data entry allows individual equipment footprint record.
- Auto 99 test logging, set up via hand set.
- Worldwide service and technical support.
- Re-calibration - Annual certification by an approved Parker Service Centre.



# LCM30 Technical Specification

### Measurement

Part Number	Description
Particle Size Reporting Channels <sup>i</sup>	MTD: >4, >6, >14, >21, >25e, >30, >38 and >70e µm ACFTD: >2, >5, >10, >15, >20e, >25, >50 and >100e µm
Reporting Contamination Standards <sup>ii</sup>	ISO 4406:Code 0 to 22 NAS 1638 0 to 12 GOST 17216:00 to 17 (consult Parker) SAE AS 4059F Table 1: 00 to 12 SAE AS 4059F Table 2: 00 to 12
Other Test Methods	IP564: determination of the level of cleanliness of aviation turbine fuel  Automatic IP564 test mode to include single flush and three repeat tests - average and individual results displayed.
Reporting Repeatability.	Measured Channels: <7% at measured counts for MTD particles size 4, 6 and 14 µm <sup>iii</sup>
Calibration	MTD: Calibration in accordance with ISO 11943:Section 9 ACFTD: The LCM30 is calibrated against the Master PCM at the particle sizes shown within the specified limits  Consult Parker for re-calibration.
Test Time	< 90 seconds in both single and multi-test mode.
Test Modes	Single / Multiple - fully automated.
Moisture Sensor	Compatible with mineral oils only. Relative Humidity (%RH) ±5% RH Stability: +-2% RH typical at 50% RH in one year. Temperature [°C] -25 to +150°C ±0.9%

<sup>i</sup> = calculated channel indicated by the letter e on the handset display.  
<sup>ii</sup> = The instrument only uses the shorthand in these standards for reporting contamination levels.  
<sup>iii</sup> = 95% confidence level using an MTD distribution with a concentration of 6mg/L.



## LCM30 - Technical Data (cont)

### Operating environment

Fluid Compatibility	Mineral oils and petroleum based fluids. For other fluids consult Parker
Working Viscosity	2 to 100 cSt 2 to 200 cSt when used with LCM30 Case Mounted Pump (100 cSt when reporting in GOST standard and using Heated Bath) 2 to 500 cSt when used with Single Point Sampler Higher viscosities when used with Trace Heated Hoses
Environmental Temperature	+5°C to +40°C
Fluid Temperature	+5°C to +80°C
Working Pressure	2.5 bar when using Case Mounted Pump; up to 420 bar when CMP not used
Flow Rate	30mL/min when using Case Mounted Pump; 6 - 380 l/min max. when used with System 20 Sensors, higher with Single Point Sampler
Inlet and Outlet Fittings	M16 MINIMESS®

### Electrical

Instrument External Power	10 to 24V - 3A max.
Trace Heated Hose (THH)	12V DC 5A max - 24V DC 2.5A max.
Rechargeable Battery	12V / Capacity: 4.5Ah with - 12V Nom.
Rechargeable Battery Pack	Input Voltage: 18V DC - Input Current: 2.5A Charge Time: Typically 4.0 hours for full charge Number of Tests: Typically 320 - 450 depending on product variant and operating conditions.
Regional Plugs	UK (Type G) - EU (Type C) - US (Type B) - Australasia (Type I)

### Interface

Data Communication Port	USB B
Menu Structure and Layout	Intuitive menu structure
Case Mounted Pump (CMP)	CMP operation via handset - Automatic CMP operation when test enabled
Trace Heated Hose (THH)	Trace Heated Hose (THH) initiated via hand set.
Printer	Thermal printer

### Materials

Outer Mouldings	Mouldings: Structural foam ABS / Coating: Polyurethane
Material Wetted Flow Path	Nylon with Kevlar Reinforcement Microbore Hose / Brass / Viton / Polyacetal (Delrin) / Zinc Plated Mild Steel / Stainless Steel 302, 303 and 316 / Soda-lime Glass

### Standard product table

LCM302022	icountLCM30 (MTD calibration)
LCM302028	icountLCM30 (MTD calibration) (Case Mounted Pump)
ACC6NW005	Printer Paper Roll
ACC6NE054	LCM30 Rechargeable Battery Pack

## Supporting Products

### Universal Bottle Sampler

#### Simple and efficient offline oil sampling

The UBS provides the dynamic link to portable particle and water counters. The UBS off-line sampler has microprocess technology to recognise and adjust to the connecting monitor including the icountLCM30 and H<sub>2</sub>Oil water in oil monitor.



Part Number	Description
UBS9002	Universal bottle sampler (includes aluminium case and accessories)
UBS9003	Universal bottle sampler

### Single Point Sampler

#### Lightweight and compact connection

The SPS (Single Point Sampler) is a lightweight, compact and easy to use online sampling unit that connects an icountLCM30 or H<sub>2</sub>Oil to a single pressure test point in a fluid system. Suitable for use with mineral and biodegradable oils, petroleum based fluids, the SPS offers fingertip operated control even at high pressures - 420 bar (6000 PSI) rated maximum pressure.



Part Number	Supersedes	Description
SPS2021	SPS.2021	Single point sampler (Mineral Oil fluids)
ACC6NW003	B84784	Waste bottle (Universal)
ACC6NH001	B84224	Extension hose/coupling (Mineral fluids)
ACC6NH003	B84788	Waste hose (Mineral Oil)



# Parker Worldwide

## Europe, Middle East, Africa

**AE – United Arab Emirates,**  
Dubai

Tel: +971 4 8127100  
parker.me@parker.com

**AT – Austria,** St. Florian  
Tel: +43 (0)7224 66201  
parker.austria@parker.com

**AZ – Azerbaijan,** Baku  
Tel: +994 50 2233 458  
parker.azerbaijan@parker.com

**BE/NL/LU – Benelux,**  
Hendrik Ido Ambacht  
Tel: +31 (0)541 585 000  
parker.nl@parker.com

**BG – Bulgaria,** Sofia  
Tel: +359 2 980 1344  
parker.bulgaria@parker.com

**BY – Belarus,** Minsk  
Tel: +48 (0)22 573 24 00  
parker.poland@parker.com

**CH – Switzerland,** Etoy  
Tel: +41 (0)21 821 87 00  
parker.switzerland@parker.com

**CZ – Czech Republic,** Klecany  
Tel: +420 284 083 111  
parker.czechrepublic@parker.com

**DE – Germany,** Kaarst  
Tel: +49 (0)2131 4016 0  
parker.germany@parker.com

**DK – Denmark,** Ballerup  
Tel: +45 43 56 04 00  
parker.denmark@parker.com

**ES – Spain,** Madrid  
Tel: +34 902 330 001  
parker.spain@parker.com

**FI – Finland,** Vantaa  
Tel: +358 (0)20 753 2500  
parker.finland@parker.com

**FR – France,** Contamine s/Arve  
Tel: +33 (0)4 50 25 80 25  
parker.france@parker.com

**GR – Greece,** Piraeus  
Tel: +30 210 933 6450  
parker.greece@parker.com

**HU – Hungary,** Budaörs  
Tel: +36 23 885 470  
parker.hungary@parker.com

**IE – Ireland,** Dublin  
Tel: +353 (0)1 466 6370  
parker.ireland@parker.com

**IL – Israel**  
Tel: +39 02 45 19 21  
parker.israel@parker.com

**IT – Italy,** Corsico (MI)  
Tel: +39 02 45 19 21  
parker.italy@parker.com

**KZ – Kazakhstan,** Almaty  
Tel: +7 7273 561 000  
parker.easteurope@parker.com

**NO – Norway,** Asker  
Tel: +47 66 75 34 00  
parker.norway@parker.com

**PL – Poland,** Warsaw  
Tel: +48 (0)22 573 24 00  
parker.poland@parker.com

**PT – Portugal**  
Tel: +351 22 999 7360  
parker.portugal@parker.com

**RO – Romania,** Bucharest  
Tel: +40 21 252 1382  
parker.romania@parker.com

**RU – Russia,** Moscow  
Tel: +7 495 645-2156  
parker.russia@parker.com

**SE – Sweden,** Borås  
Tel: +46 (0)8 59 79 50 00  
parker.sweden@parker.com

**SK – Slovakia,** Banská Bystrica  
Tel: +421 484 162 252  
parker.slovakia@parker.com

**SL – Slovenia,** Novo Mesto  
Tel: +386 7 337 6650  
parker.slovenia@parker.com

**TR – Turkey,** Istanbul  
Tel: +90 216 4997081  
parker.turkey@parker.com

**UA – Ukraine,** Kiev  
Tel: +48 (0)22 573 24 00  
parker.poland@parker.com

**UK – United Kingdom,** Warwick  
Tel: +44 (0)1926 317 878  
parker.uk@parker.com

**ZA – South Africa,** Kempton Park  
Tel: +27 (0)11 961 0700  
parker.southafrica@parker.com

## North America

**CA – Canada,** Milton, Ontario  
Tel: +1 905 693 3000

**US – USA,** Cleveland  
Tel: +1 216 896 3000

## Asia Pacific

**AU – Australia,** Castle Hill  
Tel: +61 (0)2-9634 7777

**CN – China,** Shanghai  
Tel: +86 21 2899 5000

**HK – Hong Kong**  
Tel: +852 2428 8008

**IN – India,** Mumbai  
Tel: +91 22 6513 7081-85

**JP – Japan,** Tokyo  
Tel: +81 (0)3 6408 3901

**KR – South Korea,** Seoul  
Tel: +82 2 559 0400

**MY – Malaysia,** Shah Alam  
Tel: +60 3 7849 0800

**NZ – New Zealand,** Mt Wellington  
Tel: +64 9 574 1744

**SG – Singapore**  
Tel: +65 6887 6300

**TH – Thailand,** Bangkok  
Tel: +662 186 7000

**TW – Taiwan,** Taipei  
Tel: +886 2 2298 8987

## South America

**AR – Argentina,** Buenos Aires  
Tel: +54 3327 44 4129

**BR – Brazil,** Sao Jose dos Campos  
Tel: +55 800 727 5374

**CL – Chile,** Santiago  
Tel: +56 2 623 1216

**MX – Mexico,** Toluca  
Tel: +52 72 2275 4200

### EMEA Product Information Centre

Free phone: 00 800 27 27 5374

(from AT, BE, CH, CZ, DE, DK, EE, ES, FI, FR, IE, IL, IS, IT, LU, MT, NL, NO, PL, PT, RU, SE, SK, UK, ZA)

### US Product Information Centre

Toll-free number: 1-800-27 27 537

[www.parker.com](http://www.parker.com)